



Safety Data Sheet according to Regulation (EC) 'No. 2015/830

SECTION 1: Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier	01736GBE	Revision Date:	18/02/2022
Product Name:	STONCLAD GS - B	Supersedes Date:	18/11/2019
		Version Number:	8
UFI Code:	No Information		
1.2 Relevant identified uses of the substance or mixture and uses advised against	For use by appropriately trained applicators. Component of multicomponent coatings - Professional use only. Please see Technical Data Sheet.		
1.3 Details of the supplier of the safety data sheet			
Importer:	None		
Manufacturer:	Stonhard Europe 9 Rue du Travail 1400 Nivelles Belgium		
	Regulatory / Technical Information: +32 67493710 Nivelles, Belgium		
Datasheet Produced by:	ehs-eu@stonhard.com		
1.4 Emergency telephone number:	CHEMTREC +1 703 5273887 (Outside US) PPC +1 412 6816669 (Outside US) Centro Antiveleni di Milano Tel+39 02 66101029 (CAV - Grande Ospedale Metropolitano Niguarda - Milano)(24h/24h) Emergenza ambientale +39 335-601 32 88 / +39 347-949 84 88 / +39 348-246 90 99		

SECTION 2: Hazard Identification

2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

HAZARD STATEMENTS

Other EU extensions	EUH205
Skin Irritation, category 2	H315
Skin Sensitizer, category 1	H317
Eye Irritation, category 2	H319
Hazardous to the aquatic environment, Chronic, category 2	H411

2.2 Label elements

Symbol(s) of Product



Signal Word

Warning

Named Chemicals on Label

Oxirane, mono[(C13-15-alkyloxy)methyl] derivs, Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

HAZARD STATEMENTS

Other EU extensions	EUH205	Contains epoxy constituents. May produce an allergic reaction.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Hazardous to the aquatic environment, Chronic, category 2	H411	Toxic to aquatic life with long lasting effects.

PRECAUTION PHRASES

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

No information

SECTION 3: Composition/Information On Ingredients

3.2 Mixtures

Hazardous ingredients

<u>Name According to EEC</u>	<u>EINEC No.</u>	<u>CAS-No.</u>	<u>%</u>	<u>Classifications</u>	
Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	500-033-5	25068-38-6	75-100	H315-317-319-411	Aquatic Chronic 2, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1
Oxirane, mono[(C13-15-alkyloxy)methyl] derivs	939-183-5		10 - <25	H317-411	
hydrocarbons, c10, aromatics, <1% naphthalene	918-811-1	1189173-42-9	2.5 - <10	H304-336-411	Aquatic Chronic 2, Asp. Tox. 1, Skin Cracking, STOT SE 3 NE

p-mentha-1,4(8)-diene 205-341-0 138-86-3 <0.1 H226-315-317-410

<u>CAS-No.</u>	<u>M-Factors</u>	<u>REACH Reg No.</u>
25068-38-6		01-2119456619-26
		01-2119962192-39
1189173-42-9		01-2119463583-34
138-86-3	1	

Remarks: CAS No. 25068-38-6 identified as CAS No. 1675-54-3, EC No. 216-823-5 under REACH Registration

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

SECTION 4: First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

No Information

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

SECTION 5: Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. High volume water jet. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Contains epoxy constituents. See information supplied by the manufacturer.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains. May cause long-term adverse effects in the aquatic environment.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

FURTHER INSTRUCTIONS: Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

SECTION 7: Handling and Storage**7.1 Precautions for safe handling**

Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: No Information

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

SECTION 8: Exposure Controls/Personal Protection**8.1 Control parameters****Ingredients with Occupational Exposure Limits (IR)**

<u>Name</u>	<u>CAS-No.</u>	<u>LTEL ppm</u>	<u>STEL ppm</u>	<u>STEL mg/m3</u>	<u>LTEL mg/m3</u>
Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	25068-38-6				
Oxirane, mono[(C13-15-alkyloxy)methyl] derivs					
hydrocarbons, c10, aromatics, <1% naphthalene	1189173-42-9				
p-mentha-1,4(8)-diene	138-86-3				

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls**Personal Protection**

RESPIRATORY PROTECTION: The mixing and application process for this material has been assessed to determine levels of worker exposure to airborne vapors. The findings demonstrate that workers are not exposed to concentrations of airborne vapors which exceed the set regulatory exposure limits. Ensure adequate ventilation in enclosed or confined spaces. No personal respiratory protective equipment normally required.

EYE PROTECTION: Safety glasses.

HAND PROTECTION: Impervious gloves. Protective gloves complying with EN 374. Long sleeved clothing. Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

Chemical Name:

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

EC No.:

500-033-5

CAS-No.:

25068-38-6

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required					0.75 mg/kg bw/day		0.75 mg/kg bw/day
Inhalation		12.25 mg/m3		12.25 mg/m3				
Dermal		8.33 mg/kg bw/day		8.33 mg/kg bw/day		3.571 mg/kg bw/day		3.571 mg/kg bw/day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.006 mg/l
Fresh water sediments	0.996 mg/L
Marine water	0.0006 mg/l
Marine sediments	0.0996 mg/kg
Food chain	
Microorganisms in sewage treatment soil (agricultural)	0.196 mg/kg
Air	

Chemical Name:

hydrocarbons, c10, aromatics, <1% naphthalene

EC No.:

918-811-1

CAS-No.:

1189173-42-9

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							7.5 mg/kg bw/day
Inhalation				151 mg/m3				32 mg/m3
Dermal				12.5 mg/kg bw/day				7.5 mg/kg bw/day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	
Fresh water sediments	
Marine water	
Marine sediments	
Food chain	
Microorganisms in sewage treatment soil (agricultural)	
Air	

SECTION 9: Physical and Chemical Properties**9.1 Information on basic physical and chemical properties**

Appearance:	PALE YELLOW
Physical State	LIQUID
Odor	FAINT EPOXY ODOR
Odor threshold	n/a
pH	n/a

Melting point / freezing point (°C)	Not determined
Boiling point/range (°C)	120 - 120
Flash Point, (°C)	94
Evaporation rate	Not determined
Flammability (solid, gas)	n/a
Upper/lower flammability or explosive limits	n/a - n/a
Vapour Pressure	<1.0 mmHg
Vapour density	n/a
Relative density	1.07
Solubility in / Miscibility with water	insoluble
Partition coefficient: n-octanol/water	n/a
Auto-ignition temperature (°C)	n/a
Decomposition temperature (°C)	n/a
Viscosity	400 cps
Explosive properties	n/a
Oxidising properties	n/a

9.2 Other information

VOC Content g/l:	40.00
Grams of VOC per liter of coating product as applied per ISO 11890-1 and/or ISO 11890-2.	
Specific Gravity (g/cm³)	1.07

SECTION 10: Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

No decomposition if stored and applied as directed. Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

No Information

10.5 Incompatible materials

Strong oxidizing agents. Acids and bases. Amines.

10.6 Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapours. Alcohols. Exothermic reaction. Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50:	No Information
Inhalation LC50:	No Information

Irritation: No information available.

Corrosivity: No information available.

Sensitization:	No information available.
Repeated dose toxicity:	No information available.
Carcinogenicity:	No information available.
Mutagenicity:	No information available.
Toxicity for reproduction:	No information available.
STOT-single exposure:	No information available.
STOT-repeated exposure:	No information available.
Aspiration hazard:	No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested.
Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>	<u>Gas LC50</u>	<u>Dust/Mist LC50</u>
25068-38-6	Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	5000 mg/kg (oral-rat)	>2000 mg/kg (dermal, rat M-F)	No information	No information	No information
1189173-42-9	hydrocarbons, c10, aromatics, <1% naphthalene	>7050 mg/kg (LD50, oral, rat)	>2000 mg/Kg (LD50, Dermal, rabbit)	>4688 mg/m3 (LC50, Vapor, rat)	No information	No information
138-86-3	p-mentha-1,4(8)-diene	5,300 mg/kg (rat)			0.000	0.000

Additional Information:

No Information

SECTION 12: Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):	No information
IC50 72hr (Algae):	No information
LC50 96hr (fish):	No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB assessment: No information

12.6 Other adverse effects: No information

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
25068-38-6	Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	1.8 mg/l (Daphnia magna, EC50, 48h,static)	11 mg/l (Scenedesmus capricornutum,EC50r, 72h)	1.5 mg/L (Rainbow trout), 3.6 mg/L (fish)
	Oxirane, mono[(C13-15-alkyloxy)methyl] derivs	No information	No information	No information
1189173-42-9	hydrocarbons, c10, aromatics, <1% naphthalene	>=3-<=10 mg/L (Daphnia magna)	>=1-<=3 mg/L (Pseudokirchneriella subcapitata)	>=2-<=5 mg/L (Oncorhynchus mykiss)

138-86-3 p-mentha-1,4(8)-diene

17 mg/l

No information

80 mg/l

SECTION 13: Disposal Considerations

13.1 WASTE TREATMENT METHODS: If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

European Waste Code: 080111*

Packaging Waste Code: 150110

SECTION 14: Transport Information

14.1 UN number	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Technical name	Reaction product:bisphenol-a-(epichlorhydrin) epoxy resin
14.3 Transport hazard class(es)	9
Subsidiary shipping hazard	Shipping Hazard (Marine Pollutant)
14.4 Packing group	III
14.5 Environmental hazards	Shipping Hazard (Marine Pollutant)
14.6 Special precautions for user	Not applicable
EmS-No.:	F-A, S-F
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Not applicable

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:

Denmark Product Registration Number: Not available

Danish MAL Code: 0 - 5

Danish MAL Code - Mixture: 5 - 6

Sweden Product Registration Number: Not available

Norway Product Registration Number: Not available

Germany WGK Class: 3

Directive 2004/42/CE : 40

Covered by Directive 2012/18/EC (Seveso III): E2

Restrictions to product or to substances according to Annex XVII, Regulation (CE) 1907/2006: Entry 3, 40

Annex XIV - Authorisation List:

CAS-No. Name According to EEC

Not Applicable

SVHC - Substances of very high concern (Candidate List):

CAS-No. Name According to EEC

Not Applicable

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other Information**Text for CLP Hazard Statements shown in Section 3 describing each ingredient:**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Reasons for revision

Substance and/or Product Properties Changed in Section(s):

- 01 - Identification
- 08 - Exposure Controls/Personal Protection
- 11 - Toxicological Information
- 12 - Ecological Information
- 15 - Regulatory Information

Substance Hazard Threshold % Changed

Revision Statement(s) Changed

This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark;
 European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830;
 European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP);
 EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

Acronym & Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m ³	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram

N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC	International Bulk Container
RTI	Respiratory Tract Irritation
NE	Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.

